



"WET LOOK II" SEALER

FOR CONCRETE, MASONRY & NATURAL STONE

FORMULATED SPECIFICALLY TO PROTECT AND GIVE A "WET LOOK" APPEARANCE

PRODUCT DESCRIPTION

Glaze 'N Seal "Wet Look II" is a low VOC water-based sealer designed to give the surface that deepened "wet look" appearance. It may be used indoors or outdoors and is extremely easy to apply and maintain. "Wet Look II" is a quick-drying, non-yellowing formula that protects against oil and grease.

USES

"Wet Look II" protects and beautifies all decorative concrete surfaces, exposed aggregate, pavers, masonry and natural stone. It is ideal for driveways, patios and interior floors.

FEATURES

- Deepened "Wet Look" Appearance
- Repels Oil and Grease Stains
- Eligible for LEEDS points
- Non-Flammable
- Meets all VOC Regulations
- Blush Resistant
- Cleans up with Water
- Easy to Apply
- Recoatable
- Never Yellows
- Breathable

PREPARATION

All surfaces must be free of efflorescence, dirt, oil, wax, grease and defective paint or sealer. If acid has been used, neutralize surface with a product like Glaze 'N Seal Neutralizing Rinse and allow surface to dry thoroughly before applying sealer. When water is used or surface is wet from rain, allow surface to dry 24-48 hours before sealing.

APPLICATION

Important Note: Always Test a small area of the surface to be sealed to verify penetration and satisfaction of sealed appearance.

Do not shake container. Apply two or more thin coats of sealer (do not allow to puddle). Sealer can be applied with brush lamb's wool applicator, roller or spray equipment. Make sure each coat is dry to the touch before applying second coat; usually one to three hours. Allow additional drying time in moist climates. Apply between 55° and 80°F. Do not apply if rain is expected within 24-hours. Suitable for light traffic after 24-hours. Avoid heavy traffic or autos for 72-hours.

SPECIFICATIONS

Base	Aqueous Acrylic Copolymer
Tukon Hardness	+6.0
Friction Level	Excess 6.5
Glass Transition Point	34C
Density	8.7 lbs. per gallon
Refractive Index	Approx. 1.4077
Solids	Excess 16%
Appearance	Milky White — Dries Clear
VOC	Less than 100 grams per liter

Coverage: 150-300 sq. ft. per gallon (varies based on surface porosity). Second coat coverage is 50% greater.

Dry Time: Dry to touch in 1-hour, recoat in 2-hours. Allow foot traffic in 24-hours, vehicular traffic in 72-hours (77°F, 50% RH).

Clean-up and Storage: Clean all tools immediately after use with soap and water. Store unused product in a dry place above 50°F. Do not use solvent-based cleaners on surface. For added protection indoors use Glaze 'N Seal Floor Polish (High-Gloss or Matte) to extend the life of the sealer.



Quality Products for Concrete, Tile and Masonry

Glaze 'N Seal Products, Irvine, CA • 800/486-1414
www.glaze-n-seal.com

FS 12-8/10