



ACRYLIC FLOOR POLISH

FORMULATED ESPECIALLY FOR QUARRY TILE • MEXICAN & PAVER TILE • SLATE • FLAGSTONE COLORED & HARD TROWELED CONCRETE • BRICK • TERRAZZO STAMPED CONCRETE • FRENCH PROVINCIAL TILE

PRODUCT DESCRIPTION

Glaze 'N Seal Floor Polish is a product of revolutionary new chemistry, designed to produce a high gloss finish with extreme protection against foot traffic, abrasion and scuffing, on difficult floor surfaces.

FEATURES

- **Made specifically for Tile and Masonry Type Surfaces.**
- **High Initial gloss and superior rated gloss retention.**
- **Slip Resistance: Excellent. Coefficient of friction exceeds 0.5.**
- **Economy: Easily applied, self polishing finish that can also be buffed.**
- **Wear resistance 5-7 KHN, compared to industry standards of 2-4 KHN.**

PRODUCT INFORMATION

Glaze 'N Seal Floor Polish is an acrylic Polymer floor finish that can be applied and reapplied with ease. The more coats, the higher the gloss and greater the protection. **Glaze 'N Seal Floor Polish** can be repaired (heavy foot traffic areas, etc.) without redoing the entire floor.

PREPARATION

Floor surfaces should be clean and dry. Remove all dirt, defective waxes, coatings and efflorescence on masonry type surfaces. Porous surfaces and grout must be pre-sealed with a **Glaze 'N Seal** sealer (Lacquer, Multipurpose Sealer or Olé) prior to application of Floor Polish. Floor Polish acts as a protective traffic coating to protect the sealer and substrate. On some dense floors, polish may be applied directly to the surface.

DO NOT APPLY DIRECTLY TO POROUS SURFACES.

APPLICATION PROCEDURE

Apply **Glaze 'N Seal Floor Polish** with a sponge mop, soft cloth or standard wax applicator. Two or more light coats should be applied initially. Avoid creating excess foam when sponge is used. Do not puddle polish. Allow the first coat 30-50 minutes until dry "to the touch" before applying second coat. Additional coats will give additional protection and gloss.

MAINTENANCE/REPAIR

Do not allow polish to wear through. To clean: damp mop finished surface with plain water regularly. Occasionally add 2-4 ounces of **Glaze 'N Seal Neutral Cleaner** to wash water to aid cleaning of oily dirt and soil pickup. Alkaline cleaners may dull surface. Do not allow other cleaning agents onto finished floor. **Glaze 'N Seal Acrylic Floor Polish** may be repaired when scratched or worn by reapplication to the affected areas only. It is normally not necessary to treat the entire area.

STRIPPING

This is normally not required as this non-yellowing formula can last for years when maintained as directed. Polish, if necessary, can be removed with Alkaline cleaner or ammonia and water.

COVERAGE

Coverage should average 300 to 1000 square feet per gallon, dependent on porosity of surface.

LIMITATIONS

Do not shake or stir. Do not allow to freeze in its liquid state. Recommended for nonabsorbent surfaces only.



Quality Products for Concrete, Tile and Masonry

Glaze 'N Seal Products, Irvine, CA

FS42 3/01