



STAIN RESISTANT – WATER REPELLENT ACRYLIC GROUT SEALER

**CLEAR WATERBASED ALL ACRYLIC FINISH AND SEALER
DESIGNED TO ELIMINATE STANDING AND WATER PENETRATION ON
CEMENT BASE GROUTS AND MORTARS. PROTECTS AGAINST ALL
ORGANIC STAINS INCLUDING COOKING OIL, GREASE, AND BEVERAGES**

USES

- Use on colored or plain cement based mortars.
- Use Indoors or outdoors.
- Use on any grout where there is a concern about stains or water penetration.
- Use on any grout surface where sanitation and dirt rejection is important.
- Use anywhere that other grout sealers have failed (after complete removal of failed sealer).

PREPARATION

Grout must be completely free of grease, oils, food stains, mildew and efflorescence. Also, **remove all cleaning residue**. Do not apply this sealer over acid cleaned surfaces without neutralizing first, or over silicone sealers. Ask your dealer about recommended cleaning products.

SPECIAL FEATURES

- Grout wipes clean as easily as the tile.
- Best stain resistance of any water based grout sealer.
- Safe to use in cooking, eating, and food preparation areas.
- Shower and bathroom cleaning become a breeze.
- Makes every tile surface a sanitary surface.
- Stands up to ammoniated household cleaners.

STORAGE: Do not allow to freeze.

FEATURES

- NONFLAMMABLE
- LONG LASTING
- REPELS STAINING
- WATER REPELLENT
- RECOATABLE
- CLEANS UP WITH WATER

Prior to application, apply sealer to a small test area to verify sealer penetration and satisfaction of appearance. May affect color of grout slightly. **Do not** apply over silicone sealed grouts. On freshly grouted areas, wait 24 hours before applying sealer. Allow fresh grout to cure before applying any *additional* coats of sealer. Apply one light coat directly to grout joint with a small brush or sponge brush. Avoid overlapping on tile and puddling on grout. Use a clean, damp sponge every few minutes to wipe excess sealer from tile face. **Do not** allow to dry on tile. Two or more coats may be necessary in food preparation areas or on very porous grout. Dry 1-4 hours between coats. Wait 24 hours before using sealed area.

SPECIFICATIONS

TUKON HARDNESS	+5.9
GLASS TRANSITION RATE	33.8C
DENSITY	8.56 pounds per gallon
APPEARANCE	Milky White – Dries Clear
DRY TIME	1 to 4 hours
CURE TIME	3 to 5 days



Quality Products for Concrete, Tile and Masonry

Glaze 'N Seal Products, Irvine, CA

FS 41-5/99