

**MATERIAL SAFETY DATA SHEETS****SECTION 1 PRODUCT IDENTIFICATION**

PRODUCT NAME: **GLAZE `N SEAL WET LOOK II SEALER**  
 PRODUCT CLASS: CLEAR FINISH  
**GLAZE `N SEAL PRODUCTS 18207 E. McDermott St. Ste. C Irvine, CA 92614-6711**  
 EMERGENCY TELEPHONE NUMBERS:  
 Day/Night: Chemtrec (800) 424-9300  
 INFORMATION TELEPHONE: (800) 486-1414  
 Date of Preparation: 9/2/00 Rev. 8/20/02

**SECTION 2 INGREDIENTS**

INGREDIENT	CAS NUMBER	WT. %	OCCUPATIONAL EXPOSURE LIMITS	
			OSHA PEL	TLV
Ethylene Glycol Monobutyl Ether	111-76-2	≤ 5	25ppm	25ppm
Diethylene Glycol Monobutyl Ether	29911-28-2	≤ 1	N/A	N/A

**SECTION 3 PHYSICAL DATA**

BOILING RANGE: 210-447°F VAPOR DENSITY (air=1): heavier than air.  
 EVAPORATION RATE: Slower than Ether % VOLATILE VOLUME: 83  
 WT./GALLON: 8.47 lb. VOC: 220 G/L

**SECTION 4 FIRE & EXPLOSION HAZARD DATA**

FLASH POINT: > 200°F  
 FLAMMABILITY CLASSIFICATION: Non-combustible. DOT Not Regulated.  
 EXTINGUISHING MEDIA: Foam, Dry Chemical, CO2.  
 USUAL FIRE & EXPLOSION HAZARD: Material can splatter over 100°C/212°F Polymer film can burn.  
 SPECIAL FIREFIGHTING PROCEDURES: Wear self-contained breathing apparatus with a full facepiece operated in the positive pressure demand mode and full body protection when fighting fires.

**SECTION 5 HEALTH HAZARD DATA**

**EFFECTS OF OVEREXPOSURE:**  
Inhalation: Vapor or mist can cause irritation of the respiratory system, experienced as nasal discomfort & discharge, with chest pain & coughing. Headache, nausea, vomiting & dizziness may occur.  
Eye Contact: Causes moderate irritation, experienced as discomfort or pain, excess blinking & tear.  
Skin Contact: Slightly irritating to the skin. May cause local itching & redness after prolonged contact.

**EMERGENCY & FIRST AID PROCEDURES:**

Inhalation: Remove to fresh air. Seek medical attention.  
Eye & Skin Contact: Immediately flush eyes with water for 15 minutes. Contact a physician if irritation persists. Wash affected skin areas with soap and water.  
Swallowing: If patient is conscious, give two glasses of water. Obtain medical attention.

**SECTION 6 REACTIVITY DATA**

STABILITY: Stable.  
 HAZARDOUS POLYMERIZATION: Will not occur.  
 HAZARDOUS DECOMPOSITION PRODUCTS: Burning can produce acrylic monomers, carbon dioxide and/or carbon monoxide.  
 CONDITIONS TO AVOID: Avoid temperatures above 177°C (350°F) the onset of polymer decomposition.  
 INCOMPATIBILITY MATERIALS TO AVOID: Strong oxidants.

**SECTION 7 SPILL OR LEAK PROCEDURE**

Floor may be slippery: use care to avoid falling. Remove all sources of ignition.  
 SMALL SPILL: Absorb spill with inert material (e.g. sand, cat litter, oil dri, etc.) Collect absorbed materials and place in container. Rinse affected area thoroughly with water.  
 LARGE SPILL: Dike an contain spill with inert material (e.g. sand, cat litter, oil dri, etc.) Transfer liquid to containers for recovery or disposal and solid diking materials to separate containers for disposal. Remove contaminated clothing promptly & wash affected skin areas with soap & water. Wash clothing before reuse. Keep spills & cleaning runoffs out of municipal sewers and open bodies of water.  
 WASTE DISPOSAL METHOD: Dispose of in accordance with all local, state and federal regulations.

**SECTION 8 SAFE HANDLING AND USE INFORMATION**

RESPIRATORY PROTECTION: None required if good ventilation is maintained. Otherwise a NIOSH approved respirator should be worn.  
 VENTILATION: Local and exhaust, adequate volume and pattern to avoid vapor limit above TLV.  
 PROTECTIVE GLOVES: required for prolonged use. Impermeable type (e.g. natural rubber, butyl rubber or neoprene) are recommended.  
 EYE PROTECTION: Use of safety glasses is recommended.  
 OTHER PROTECTIVE EQUIPMENT: To prevent repeated or prolonged skin contact, wear impervious clothing and boots.  
 WORK HYGIENIC PRACTICES: Wash hands thoroughly before eating or smoking. Eyewashes and safety showers are recommended in the workplace.

**SECTION 9 SPECIAL INSTRUCTIONS**

**PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:** Store at between 40°F and 120°F. Keep from freezing.  
**KEEP OUT OF REACH OF CHILDREN.**  
 The information contained herein is to the best of our knowledge and belief, accurate and reliable as of the date compiled. However, no representation, warranty, or guarantee is made as to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself or herself as to the suitability and completeness of such information for his or her own particular use.  
**WE DO NOT ACCEPT LIABILITY FOR ANY LOSS OR DAMAGES THAT MAY OCCUR FROM THE USE OF THIS INFORMATION.**