

MATERIAL SAFETY DATA SHEETS**FOR COATING, RESINS AND RELATED MATERIALS**

MANUFACTURER: GLAZE `N SEAL PRODUCTS
18207 E. McDermott St. Ste. C
Irvine, CA 92614-6711

EMERGENCY TELEPHONE NUMBERS:
Day/Night: Chemtrec (800) 424-9300

INFORMATION TELEPHONE: (800) 486-1414

Date of Preparation: 9/2/00 Rev. 3/17/03

SECTION 1 PRODUCT IDENTIFICATION

PRODUCT NAME: **Glaze `N Seal "Wet Look" 2000 Lacquer**
PRODUCT CLASS: CLEAR ACRYLIC LACQUER

SECTION II HAZARDOUS INGREDIENTS

<u>INGREDIENT</u>	<u>CAS NUMBER</u>	<u>WT. %</u>	<u>OCCUPATIONAL EXPOSURE LIMITS</u>
Pyroacetic Ether	67641	20-40%	750 PPM
Mixed Petroleum Hydro-carbon	64742-89-8	5-20%	375 PPM
4 Chlorobenzotrifluoride	98566	20-40%	Not Established
1 Methoxy Propanol Acetate	108656	1-15%	Not Established

SECTION III HMIS HAZARD RATINGS

Health Hazard 1 Fire Hazard 3 Reactivity 0

SECTION IV PHYSICAL DATA

BOILING RANGE: 280-399°F EVAPORATION RATE: (BuAc=) 1.0
VAPOR DENSITY: Heavier than air % VOLATILE VOLUME: 78
WT/GALLON: 7.7 lbs VOC: 395 g/l of coating

SECTION V FIRE & EXPLOSION HAZARD DATA

FLAMMABILITY CLASSIFICATION: OSHA FLAMMABLE LIQUID-UN 1263; Packing Group II
FLASH POINT: 37°F T.C.C.
EXTINGUISHING MEDIA: Foam, Alcohol Foam, CO₂, Dry Chemical.
USUAL FIRE AND EXPLOSION HAZARD: Keep away from heat, sparks and open flame. Do not smoke. Vapors may ignite explosively. May cause flash fire.
SPECIAL FIREFIGHTING PROCEDURES: Wear self-contained breathing apparatus with a full facepiece operated in the pressure demand mode and full body protection when fighting fires.

SECTION VI HEALTH HAZARD DATA**EFFECTS OF OVEREXPOSURE**

INHALATION: Temporary dizziness, headache, possible nausea. Symptoms disappear when exposure ceases. Eye or skin contact may cause discomfort by de-fatting action of solvent.

MEDICAL CONDITIONS PRONE TO AGGRAVATION BY EXPOSURE: Dermatitis, nausea, vomiting.

PRIMARY ROUTE(S) OF ENTRY: Dermal, inhalation, ingestion.

EMERGENCY AND FIRST AID PROCEDURES: Remove patient to fresh air. Flush eyes with clean water for 15 minutes. Contact a physician.

SECTION VII REACTIVITY DATA

STABILITY: Stable

HAZARDOUS POLYMERIZATION: Will not occur.

HAZARDOUS DECOMPOSITION PRODUCTS: Usual products of combustion including carbon dioxide and carbon monoxide.

CONDITIONS TO AVOID: Poor ventilation, excessive heat.

INCOMPATIBILITY (MATERIALS TO AVOID): Strong oxidants.

SECTION VIII SAFE HANDLING AND USE INFORMATION

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Remove all sources of ignition. Absorb with inert material and dispose in an approved manner.

WASTE DISPOSAL METHOD: Dispose in accordance with all Local, State and Federal regulations.

SECTION IX SAFE HANDLING AND USE INFORMATION

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Remove all sources of ignition. Absorb with inert material and dispose in an approved manner.

WASTE DISPOSAL METHOD: Dispose in accordance with all Local, State and Federal regulations.

SECTION X SPECIAL INSTRUCTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: Do not store above 120°F. Ground all containers. Do not take internally.

KEEP OUT OF REACH OF CHILDREN.

The information contained herein is to the best of our knowledge and belief, accurate and reliable as of the date compiled. However, no representation, warranty, or guarantee is made as to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself or herself as to the suitability and completeness of such information for his or her own particular use.

WE DO NOT ACCEPT LIABILITY FOR ANY LOSS OR DAMAGE THAT MAY OCCUR FROM THE USE OF THIS INFORMATION.